

NVD-HD3750GIM

3.0Megapixel HD Network Vandalproof IR Outdoor Dome Camera

FEATURE

- Low illumination Dome Camera
- H.26 H.264/M-JPEG, Support Multiple Code Stream
- HDTV 3MP Full Real time Transmission
- Support ONVIF, Built-in Auto Double Filter Switching Mechanism, True Day/Night
- Support 3D DNR, Mobile Surveillance, IR 40M&24pcs IR LED, Vandal proof IK10&IP66(Anti-Reflection, Scratch-Proof)
- Support WDR, DC12V/AC24V/POE



SPECIFICATION

| | | | |
|----------------------------|---------------------------------------|---|--|
| Model | Model No. | NVD-HD3750GIM | |
| | Type | 3MP HD Network Starlight Vandalproof IR Outdoor Dome Camera | |
| Camera | Sensor | 1/2.8"Progress Scan CMOS | |
| | Resolution | 2048*1536, 1920*1080, 1280*720,704*576, 640*480, | |
| | Main Stream | | |
| | Sub Stream | | |
| | Min. Illumination | color 0.001Lux@F1.2; B/W ON) 40M, 24 IR LED | |
| | IR Distance | | |
| | S/N Ratio | ≥52db | |
| | WDR | ≥100db | |
| | Electronic Shutter | 1/10000 sec. | |
| Audio/ Video Setting | Lens | 2.8mm/3.6mm Fix Lens | |
| | Day & Night | IR Cut Optical Filter | |
| | Video Compression | H.265,H.264/M-JPEG, Support Multiple Code Stream | |
| | Code Stream | 32Kbps-16Mbps, Support CBR/VBR | |
| | Video Adjustment | Brightness/ Contrast / Chroma/ Saturation/ Sharpness / GAMMA | |
| | Intelligent Features | Intelligent Code Stream, Video Mask ,Intelligent Switch Control | |
| | Image Flip | Horizontal, Vertical, Horizontal& Vertical | |
| | Motion Detection | Support | |
| | Privacy Mask | Support | |
| | 3D DNR | High/Medium/Low | |
| | OSD Setting | Support Channel Name, Date Time, Code Stream Overlay | |
| | Network | Interface | 10/100 M Ethernet (RJ-45) |
| | | Protocol | TCP/IP, UDP, RTP, RTSP, RTCP, HTTP, DNS, DHCP, FTP, NTP, PPPOE, SMTP, UPNP |
| ONVIF | | onvif 2.4 | |
| Access Control | | Administer and Common User | |
| Web Browser | | IE 6.0 and Above | |
| Max. User Number | | ≤10 | |
| Interface | CVBS/BNC | No | |
| | Audio I/O | Optional | |
| | Alarm I/O | Optional | |
| | RS485 | Optional | |
| | TF card | Optional | |
| | Mobile Surveillance | Support | |
| General | IP Grade | IP 66 | |
| | 1K Grade | 1K 10 | |
| | Working Conditions | -20°C +60°C; 10% to 90%, (Non-Condensing) | |
| | Power Supply | DC12V/AC24V/POE | |
| | Dimension(mm) Weight(with package) | 980g | |

For Financial, Prison, Supermarket, Telecom, Government, School, Airport, Factory, Hotel and Other Indoor /Outdoor Places.

Dimension (Unit : mm)

