

**JNC-41D2F36I15V  
JNZ-41D2F36I30V  
AHD Dome Camera**



**Features:**

1. 2.0MP AHD;
2. Image sensor SOIH62, Output AHD/TVI/CVI/CVBS, Effective resolution is 1080\*1920 ;
3. OSD menu supports 12 different languages; with strong light inhibition/privacy protection, BLC/DPC, 3D noise reduction function;
4. Adopt Nextchip2433H DSP, with OSD function (mirror image, color/ white-black, PAL/NTSC);
5. AGC type, day-night effect is distinct, various day-night modes can be switched by OSD menu;
6. Support UTC, 4 in 1, switched by OSD, Enhancement adjustment supported by OSD.

**Scenarios:**

Apply to roads, warehouses, underground parking and other place which required definition picture quality.

**Specifications:**

Model	JNC-41D2F36I15V / JNZ-41D2F36I30O
Processor + Sensor	Nextchip2433H+SOIH62
Signal System	1080P
Effective Picture Elements	1280 (H) x 720 (V)
Minimum Illumination	Color: 0.01Lux @(F1.2,AGC ON),0 LUX with IR
	B&W: 0.001 Lux @ (F1.2,AGC ON),0 LUX with IR
S/N Ratio	More than 69dB
Scanning System	2:1 interface
Synchronous System	Internal, Negative sync.
Auto Electronic Shutter	1/50(1/60)S-1/100,000S
Gama Characteristic	0.45
Day and Night Function	Support IR-CUT
IR Distance	15

IR Status	Under 10Lux by CDS
IR Power On	CDS AUTO Control
Video Output	1Vp-p Composite Output(75Ω/BNC)
Auto Gain Control	Auto
Power/Current	DC12V/450mA ±10%
Lens	3.6mm fixed lens
Dimension (mm)	Φ 111×84(H)mm
Storage Temperature	-30~+60°C RH95% MAX
Operating Temperature	-10~+60°C RH95% MAX