

JNI-NB5F36I400HPW (Warm-Light)

5.0Megapixel HD Network IR Outdoor BulletCamera

FEATURE

- Low illumination Dome Camera / Starlight – Starvise Lens
- H.264 H.265 H.265+ /M-JPEG, Support Multiple Code Stream
- Sony IMX 335 Image Sensor 5MP Full Real time Transmission with True Mechanical Super WDR & HDR Technology
- Support ONVIF, Built-in Auto Double Filter Switching Mechanism, True Day/Night
- Support 3D DNR, Mobile Surveillance, IR 40M&24pcs IR LED, (Anti-Reflection, Scratch-Proof)
- with in-Built Microphone DC12V/ POE



SPECIFICATION

Model	Model No.	JNI-NB5F36I400HPW
	Type	5MP HD Network Starlight IR Out-door Bullet Camera
Camera	Sensor	1/2.8"Progress Scan CMOS
	Resolution	2536*1920 25fps , 2048*1536, 1920*1080, 1280*720,704*576, 640*480,
	Main Stream	
	Sub Stream	
	Min. Illumination	color 0.00001Lux@F1.2; B/W ON) 40M, 24 IR LED+ 5 PCS array Warm Light LED
	IR Distance	
	S/N Ratio	≥52db
	WDR	≥225db
Audio/ V ideo Setting	Electronic Shutter	1/10000 sec.
	Lens	2.8mm/3.6mm Fix Lens
	Day & Night	IR Cut Optical Filter
	Video Compression	H.265+ ,H.265,H.264/M-JPEG, Support Multiple Code Stream
	Code Stream	32Kbps-16Mbps, Support CBR/VBR
	Video Adjustment	Brightness/ Contrast / Chroma/ Saturation/ Sharpness / GAMMA
	Intelligent Features	Intelligent Code Stream, Video Mask ,Intelligent Switch Control
	Image Flip	Horizontal, Vertical, Horizontal& Vertical
	Motion Detection	Support
	Privacy Mask	Support
Network	3D DNR	High/Medium/Low
	OSD Setting	Support Channel Name, Date Time, Code Stream Overlay
	Interface	10/100 M Ethernet (RJ-45)
	Protocol	TCP/IP, UDP, RTP, RTSP, RTCP, HTTP, DNS, DHCP, FTP, NTP, PPPOE, SMTP, UPNP
	ONVIF	onvif 2.4
	Access Control	Administer and Common User
Interface	Web Browser	IE 6.0 and Above , Chorme
	Max. User Number	≤10
	CVBS/BNC	No
	Audio I/O	In-Built Microphone / Optional
	Alarm I/O	Optional
	RS485	Optional
General	TF card	Optional
	Mobile Surveillance	Support
	IP Grade	IP 55
	1K Grade	1K 10
	Working Conditions	-20°C +60°C; 10% to 90%, (Non-Condensing)
General	Power Supply	DC12V /POE
	Dimension(mm) Weight(with package)	780g

For Financial, Prison, Supermarket, Telecom, Government, School, Airport, Factory, Hotel and Other Indoor /Outdoor Places.